



POWERED by
Perkins Engine
Made in UK



POWER BRITISH LTD.

YOUR WAY FOR POWER

ATP770 DIESEL GENSET



TECHNICAL DATA SHEET

ATP770

Prime Power*	Standby Power**	Voltage/Ph	Hz/rpm***	PF
771kVA/617kW	850kVA/ 678kW	400/3Ph	50/1500	0.8

Prime power*

Unlimited hours usage with an average load factor of 80% of the published Prime power over each 24 hours period. A 10% overload is available for 1 hour in every 12 hours operation.

The generator is working normally at 55 degrees with derating

Standby power**

Limited to 500 hours annual usage with an average load factor of 80% of the published Standby power rating over each 24 hour period. Up to 300 hours of annual usage may be run continuously. No overload is permitted on Standby power.

Available in 60HZ for all voltage ratings.***

Standard Reference Conditions

Note: Standard reference conditions 40°C (104°F) Air Inlet Temp, 100m (328 ft) A.S.L. 30% relative humidity.

Diesel Generator Set	
Engine Make /Model	PERKINS 2806A-E18TTAG5
Alternator Make /Model	Leroy Somer TAL-049-C
Control Panel	DSE 7320
Base Frame / Silent Canopy	Robust Structure/ Corrosion Resistant
Circuit Breaker Type	3 Pole MCCB (4P Available as optional)
Built in Base Fuel Tank Capacity	N/A
Battery	Maintenance free Lead Acid

Dimensions	Length (cm)	Width (cm)	Height (cm)	Weight (KG)
Close Type	600	245	250	4800
Open Type	490	130	230	4325

ENGINE SPECIFICATIONS	
Engine Make Model	PERKINS 2806A-E18TTAG5
No. of Cylinders	6 vertical in-line
Cycle	4 Stroke
Aspiration	Turbocharged
Cooling Method	Water cooled Governing
Type	Electronic
Governing Class	G2 - ISO 8528 Part 1
Compression Ratio	14:1
Displacement	18.1 L
Bore/Stroke	145 x 183 mm
Dynamic Charging Alternator	55AMP, 24V

LUBRICATION SYSTEM	
Oil Filter Type	Spin-On Full Flow
Total Oil Capacity	68 L
Oil Type	API-CH-4 or ACEA E5

AIR SYSTEM	
Air Filter Type	Dry Element
Combustion Air Flow (PRP)	64 m ³ /min
Combustion Air Flow (ESP)	71 m ³ /min
Max Air Filter Intake Restriction	3.7 kPa

COOLING SYSTEM	
Total Coolant Capacity (L)	110 L
Cooling Fan Air Flow	870 m ³ / min
Radiator Fan Load	26 kW
Cooling system design	50°C
Heat Radiation to Room (PRP)	76 kW

Exhaust System	
Muffler Type	Industrial Grade
Max. Back Pressure	6 kPa
Exhaust Gas Flow (PRP/ESP)	180 m ³ / min
Exhaust Gas Temperature	≤ 430 °C

Comply with Standards
ISO 3046, BS 5514, DIN 6271, NEMA-MGI, DIN EN, BS 5000, IEC 60034, IEC 60947-2

Powered By:



ATP Gen set is reliable and premium power supply .

1. Features & Benefits:

- ATP Gen set is powered by Perkins Engine , the world leader having over 85 years of innovation and excellence, with customers support in 182 countries from 3500 outlets.
- ATP Gen set is powered by Leroy Somer France Alternator, the Global number 1 in Alternators, with over 99 years of Experience, Having 120+ active patents, in over 40 countries and over 80 service centers.
- ATP Gen set is equipped with DSE controller, one of the world's top manufacturers in UK, having over 40 years of excellence, the most advanced and user friendly controller.
- Low fuel consumption, saving on fuel spend
- Compact and rugged design, saving on transport and storage cost
- Designed to occupy less space considering critical applications and cities where space is at a premium.
- Low noise and vibration, considering critical applications where noise level matters
- Easy maintenance and long service intervals , saving on maintenance cost
- Subject to rigorous tests including load acceptance, cooling, vibration and noise level prior shipment to customer.
- Simple to operate and environment friendly in worst ambient conditions
- Equipped with built-in fuel tank sufficient for 8 to 10 hours of operations.
- Fully Engineering wide range of optional accessories available.

(Contd.)



**POWERED by
Perkins Engine
Made in UK**



POWER BRITISH LTD.

YOUR WAY FOR POWER

ATP770 DIESEL GENSET



TECHNICAL DATA SHEET

ATP770



PERKINS Engine
2806A-E18TTAG5



Leroy Somer
TAL-049-C

Engine Fuel System	
Recommended Fuel	Class A2 Diesel
Fuel Consumption Standby	180 L/hr
Fuel Consumption 100% PRP	162 L/hr
Fuel Consumption 75% PRP	118 L/hr
Fuel Consumption 50% PRP	80 L/hr


ALTERNATOR SPECIFICATIONS	
Alternator Make /Model	Leroy Somer TAL-049-C
AVR Model	R150
Number of Poles	4
Number of Winding Leads	6
Type of Bearing	Single Bearing
Insulation Class - Temp Rise	Cont. H - 125/40°C
Ingress Protection Rating	IP 23
Excitation System	Self Excited
Voltage Regulation	+ 1%
Harmonic Coefficient THF	< 2%
Tel. influence TIF	< 50
Cooling air flow	1.0 m ³ / Sec



DSE7320 MKII
AUTO START & AUTO MAINS

Controller Make & Model	DeepSea 7320
Operation Mode	AMF
Display	Graphic Back-lit LCD (132x64) pixels
Ingress Protection Rating	IP65
Binary Inputs/Outputs	9/8
Analog Inputs	4
Measurement	Vac, A, Hz, kVA, kW, Vdc
Event Log	Alarms log, Hrs log
Communication	USB

Please refer to Controller Data Sheet for more details.



ATP ENCLOSURE/CANOPY

Enclosure Type	Acoustic & Weather Proof
Drainage	Fuel and Water Drainage Provision
Transportation	Tested Single Point Lifting Facility & Forklift Pockets
Ingress Protection	IP 23
Lifting	ISO Standard Lifting
Canopy RAL Color	RAL 9010 - Powder coated
Base frame RAL Color	RAL 9011 - Powder coated
Noise Pressure level @	85 db(A)@ 7 m

2. WARRANTY POLICY:

- Power British Generator technology has a warranty 1000 hours or one year whichever occurs first, from any manufacturing defect (except for bad fuel usage or misuse). Regarding that the generator must not be working less than 60 % of the load.
- Wearing parts (filters), incorrect man-made operation, Back up Genset maintenance failures are excluded from the warranty policy
- For more details please refer to www.powerbritish.co.uk

3. DOCUMENTAION

Operation and Maintenance Manual, GAD, Wiring Diagram & FAT Report are Accompanied with Genset.

4. OPTIONAL FEATURES

A. Engine

- Heavy-Duty Air Filter
- Coolant Heater
- Lubricant Oil Heater
- Fuel and Water Separator
- Lube Oil Rotary Pump

B. Alternator

- Anti Condensation Heater
- PMG + AVR
- Double Bearing Alternator
- RTDs For Bearing and Winding

C. Cooling System:

- 55 degree Radiator
- Remote Radiator

D. Control System:

- AMF / Parallel
- Remote Annunciators
- 4 p manual/Motorized Circuit breaker

E. Automatic Transfer Switch (ATS):

- Contractor or Breaker type ATS
- Motorized changeover type ATS

F. Start Battery:

- Nickel-cadmium battery
- Maintenance-free battery
- Battery charger and selector switch
- Charging current meter

G. Exhaust Muffler:

- Residential grade
- Critical grade
- Hospital grade

H. Available for voltages :

400/230V,480/277V,380/220V,440/254V,
416/240V,220/127V, 208/120V

Power British LTD.

6-9 TheSquare, Stockley Park , Uxbridge UB11 1FW ,United Kingdom

Tel : +44 2089 29985

E-mail: info@powerbritish.co.uk



Due to continuous research & product development, we reserve the right to change specification with out notice